



Yamamoto

 Yamamoto North America



WUN275

Yamamoto North America LLC
PO Box 3264,
205 S. Lee St.
Bloomington, IL 61701



866-204-0519
8am-5pm Mon-Fri Central Time
Yamamoto-NA.com

Model No.		WUN275	
Capacity (Best Practices)		125kg	275lbs
Drum	Diameter	φ1320mm	φ52.0"
	Depth	860mm	33.9"
	L / Cubic Feet	1177L	41.6ft ³
Machine Size (Packing Size)	Height	2549mm(2550mm)	100.4"(100.4")
	Width	2109mm(2280mm)	83.0"(89.8")
	Depth	2601mm(2760mm)	102.4"(108.7")
Weight of empty machine		5900kg	13008lbs
Crated Weight		6000kg	13228lbs
Drum Speed	Washing Speed	20~40rpm	
	Extraction Speed	100~640	
G - Force	High Speed	303G	
Dynamic Loading	Frequency	10.7Hz	
	Dynamic floor weight	3000kg/m ²	614.7lbs/ft ²
Loading Door	Door Height	1417mm	55.8"
	Door Opening	φ800mm	φ31.5"
Power	Electrical phase, Voltage,	Three -phase, AC208V~230V, 60Hz	
	Frequency	/※ Three-phase, AC460, 60Hz	
	Full load current	65A/※ 50A	
Minimum Supply-Circuit Conductor Ampacity		80A/※ 60A	
Maximum Rating of Supply Circuit Overcurrent Protective		80A/※ 60A	
Motor Size		25HP(18.5KW)	
Cold water Supply	Connection Port	2NPT	
	Water Supply Pressure	0.1-0.3MPa ,14.5-43.5psi ,1-3bar	
Hot water Supply	Connection Port	2NPT	
	Water Supply Pressure	0.1-0.3MPa ,14.5-43.5psi ,1-3bar	
Detergent Box Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3MPa ,14.5-43.5psi ,1-3bar	
Water Drain	Connection Port	4NPT	
Compressed-Air	Connection Port	1/2"O.D.	
	Pressure	0.7-1.0MPa ,101.5-43.5psi ,7-10bar	
Steam	Supply Port	1NPT	
	Pressure	0.5-0.7MPa,72.5-101.5psi ,5-7bar	
Usage nvironment	Temperature Of Surrounding	5-45°C	41-113°F
	Humidity	30-85%	

※ WUN275 460V Specification.

