



# Yamamoto

 Yamamoto North America



## WUD60G

Yamamoto North America LLC  
PO Box 3264,  
205 S. Lee St.  
Bloomington, IL 61701



866-204-0519  
8am-5pm Mon-Fri Central Time  
Yamamoto-NA.com

Model No.		WUD60G	
Capacity(Best Practices)	Washer extractor	27.2 kg	60 lbs
	Tumble dryer	13.6 kg	30 lbs
Drum	Diameter	φ762 mm	φ30.0"
	Depth	600 mm	23.6"
	L/ Cubic Feet	273 L	9.6 cu.ft
Machine Size (Packing Size)	Height	1848(1983)mm	72.8(72.8)"
	Width	1012(1040)mm	40.0(40.9)"
	Depth	1393(1540)mm	54.8(60.6)"
Weight of empty machine (Crated Weight)		890kg(945kg)	1965lbs(2085lbs)
Drum Speed	Washing Speed	20-50 rpm	
	Extraction Speed	100-880 rpm	
G - Force	High Speed	330 G	
Dynamic Loading	Frequency	14.7 Hz	
	Dynamic floor weight	1720 kg/m <sup>2</sup>	352.3 lb/ft <sup>2</sup>
Power	Electrical Phase, Voltage, Frequency	3-phase, AC208~230V, 60Hz	
	Full load current	17A	
Minimum Supply-Circuit Conductor Ampacity		30A	
Maximum Rating of Supply Circuit Overcurrent Protective Device		30A	
Motor Size	Drum	5HP	
	Fan	1HP	
Heating System		Hot Water Supply	
Heating system of the dryer		Gas	
Cold Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Hot Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Soap Cup Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Water Drain	Connection Port	2·1/2NPT	
Dryer Gas	Supply Port	1/2NPT	
	NATURAL GAS Pressure	1.24kPa-2.61kPa (5W.C-10.5W.C)	
	L.P.GAS Pressure	2.49kPa-3.23kPa(10W.C-13W.C)	
Duct Diameter		φ200	7.87"
Gas Consumption		1.8 m <sup>3</sup> /H	63.57 ft <sup>3</sup> /h
Usage environment	Temperature Of Surrounding	5-45 °C , 41-113 °F	
	Humidity	30-85 %	
	Altitude	The machine should be installed in the altitude which is lower than 3280 ft.	

